

## Claims

1. A safety shutdown system for controlling a fluid delivery system, the fluid delivery system including a valve for selectively closing flow between a first and second fluid vessel, and an engine for driving a fluid delivery pump, the safety shutdown system comprising:
- 5 a timer activated in response to a timer activation signal for timing a countdown interval;
- a timer activation input for selectively inputting the timer activation signal to the query timer for selectively enabling the query timer;
- 10 a wireless transmitter for selectively transmitting a timer reset signal to the timer to reset the countdown interval; and
- a controller for automatically closing the valve and killing the engine if the timer times out.
- 15 2. A safety shutdown system as defined in Claim 1, wherein the timer activation input comprises:
- at least one pair of input terminals for selectively inputting the timer activation signal.
- 20 3. A safety shutdown system as defined in Claim 2, wherein the timer activation signal comprises:
- a current induced by electrically closing the input terminals to complete a query enabling circuit.
- 25 4. A safety shutdown system as defined in Claim 1, further comprising:
- one or more sensors responsive to one or more selected fluid delivery characteristics to generate the timer activation signal.
- 30 5. A safety shutdown system as defined in Claim 4, wherein the one or more sensors are selected from the group consisting of a pressure sensor for sensing fluid pressure and a flow sensor for sensing fluid flow.

6. A safety shutdown system as defined in Claim 4, wherein the one or more sensors comprise:

5 a lever motion sensor responsive to motion of a lever on the fluid delivery system.

7. A safety shutdown system as defined in Claim 1, wherein the first fluid vessel is a tank on a vehicle, and the second fluid vessel is a tank structurally separate from the vehicle.

10

8. A safety shutdown system as defined in Claim 1, further comprising: one or more function activators for activating one or more selected functions in response to a function activation signal from the wireless transmitter.

15

9. A safety shutdown system as defined in Claim 8, wherein the one or more function activators are selected from the group consisting of a throttle speed activator for selectively increasing engine speed on a vehicle, a reel rewind activator for selectively rewinding fluid hose onto a reel, and an engine kill activator for selectively shutting down the vehicle engine.

20

10. A safety shutdown system as defined in Claim 8, wherein the controller automatically turns off at least one of the one or more selected functions if the timer times out.

25

11. A safety shutdown system as defined in Claim 8, further comprising: a set of function connection terminals for selectively connecting the one or more selected functions.

30

12. A safety shutdown system as defined in Claim 1, further comprising: an alarm initiated by the controller.

13. A safety shutdown system as defined in Claim 12, wherein the alarm sounds prior to the timer timing out.

14. A safety shutdown system as defined in Claim 1, wherein the wireless transmitter transmits within a radio frequency range.

15. A safety shutdown system for controlling a fluid delivery system, the fluid delivery system including a valve for selectively closing flow between a tank on a vehicle and another tank structurally separate from the vehicle, and an engine for driving a fluid delivery pump, the safety shutdown system comprising:

a timer activated in response to a timer activation signal for timing a countdown interval;

one or more sensors responsive to one or more selected fluid delivery characteristics to generate the timer activation signal;

at least one pair of input terminals for selectively inputting the timer activation signal;

a wireless transmitter transmitting on a radio frequency for selectively transmitting a timer reset signal to the timer to reset the countdown interval;

a controller for automatically closing the valve and killing the engine if the timer times out;

an alarm for activation by the controller prior to the timer timing out; and

one or more function activators for activating one or more selected functions in response to a function activation signal from the wireless transmitter.

16. A safety shutdown system as defined in Claim 15, wherein the timer activation signal comprises:

a current provided by electrically closing the input terminals to complete a query enabling circuit.

17. A safety shutdown system as defined in Claim 15, wherein the one or more sensors are selected from the group consisting of a pressure sensor for sensing fluid pressure and a flow sensor for sensing fluid flow.

5 18. A safety shutdown system as defined in Claim 15, wherein the one or more function activators are selected from the group consisting of a throttle speed activator for selectively increasing engine speed on a vehicle, a reel rewind activator for selectively rewinding fluid hose onto a reel, and an engine kill activator for selectively shutting down the vehicle engine.

10

19. A safety shutdown system as defined in Claim 15, further comprising:  
a set of function connection terminals for selectively connecting the one or more selected functions.

15

20. A method of controlling a fluid delivery system, the fluid delivery system including a valve for selectively closing flow between a first and second fluid vessel, and an engine for driving a fluid delivery pump, the method comprising:

providing a timer having a timer activation input;

selectively inputting a timer activation signal to the timer activation input, to

20

activate the timer and begin timing a countdown interval;

selectively transmitting a timer reset signal to the timer to reset the countdown interval; and

automatically closing the valve and killing the engine if the timer times out.

25

21. A method as defined in Claim 20, wherein the timer activation input comprises:

at least one pair of input terminals for selectively inputting the timer activation signal.

30

22. A method as defined in Claim 21, wherein inputting the timer activation signal comprises:

providing a current by electrically closing the input terminals to complete a query enabling circuit.

23. A method as defined in Claim 20, further comprising:  
5 providing one or more sensors responsive to one or more selected fluid delivery characteristics; and  
selectively generating the timer activation signal in response to the sensed fluid delivery characteristics.

10 24. A method as defined in Claim 20, further comprising:  
providing one or more function activators for activating selected vehicle functions; and  
selectively transmitting a function activation signal to activate the function activators.

15 25. A method as defined in Claim 20, further comprising:  
automatically turning off at least one of the one or more selected functions if the timer times out.

20 26. A method as defined in Claim 1, further comprising:  
initiating an alarm prior to the timer timing out.